



# Standard Storage Tank Technical Information



Model	Gallons	Diameter		Height		A		B		C		D		E		Shipping Weight		
		Bare	I/J	Bare	I/J	Bare	I/J	Bare	I/J	Bare	I/J	Bare	I/J	Bare	I/J	Bare	I/J	
HET 80	80	N/A	25.25"	N/A	63.0"	N/A	9.25"	N/A	14.25"	N/A	2"	N/A	N/A	N/A	N/A	N/A	N/A	240
HET 120	119	N/A	28.0"	N/A	62.5"	N/A	10.0"	N/A		N/A		N/A		N/A		N/A	N/A	352
HET 120 ASME	119	N/A	28.00	N/A	62.50	N/A	10.00	N/A	15.00	N/A	2.50	N/A	3/4" & 1-1/4"	N/A	2.00	N/A	N/A	365
HET 200 ASME	200	N/A	32.00	N/A	77.25	N/A	11.00	N/A	17.00	N/A	2.50	N/A	3/4" & 1-1/4"	N/A	2.00	N/A	N/A	634
HET 220 ASME	220	30.00	N/A	76.00	N/A	23.25	N/A	31.25	N/A	2.50	N/A	3/4" & 1-1/4"	N/A	2.00	N/A	548	N/A	
HET 257 ASME	257	30.00	34.00	87.00	91.00	23.25	25.63	31.25	33.63	2.50	3.00	3/4" & 1-1/4"		2.00	2.50	628	904	
HET 275 ASME	318	36.00	40.00	76.00	80.00	23.25	25.63	31.25	33.63	2.50	3.00	3/4" & 1-1/4"		2.00	2.50	673	987	
HET 350 ASME	370	36.00	40.00	87.00	91.00	23.25	25.63	31.25	33.63	2.50	3.00	3/4" & 1-1/4"		2.00	2.50	770	C/F	
HET 432 ASME	432	42.00	46.00	76.00	80.00	23.25	25.63	31.25	33.63	2.50	3.00	3/4" & 1-1/4"		2.00	2.50	795	1188	
HET 500 ASME	504	42.00	46.00	88.00	92.00	23.25	25.63	31.25	33.63	2.50	3.00	3/4" & 1-1/4"		2.00	2.50	908	1329	
HET 650 ASME	658	48.00	52.00	88.00	92.00	23.25	25.63	31.25	33.63	3.00	3.00	3/4" & 1-1/4"		2.50	2.50	1346	1817	
HET 750 ASME	752	48.00	52.00	100.00	104.00	23.25	25.63	31.25	33.63	3.00	3.00	3/4" & 1-1/4"		2.50	2.50	1507	2030	
HET 1000 ASME	940	48.00	52.00	124.00	128.00	23.25	25.63	31.25	33.63	3.00	3.00	3/4" & 1-1/4"		2.50	2.50	1828	2710	
HET 1250 ASME	1189	54.0"	58.0"	124"	126.5"	25.0"	N/A	35.0"	N/A	4" FLG	N/A	1.5"	N/A	3"	N/A	2083	4660**	
HET 1500 ASME	1469	60.0"	64.0"	124"	126.5"	25.0"	N/A	35.0"	N/A	4" FLG	N/A	1.5"	N/A	3"	N/A	2784	6200**	
HET 1750 ASME	1763	60.0"	64.0"	148"	150.5"	31.0"	N/A	41.0"	N/A	4" FLG	N/A	1.5"	N/A	C/F	N/A	3267	C/F	
HET 2000 ASME	2056	60.0"	64.0"	172"	174.5"	31.0"	N/A	41.0"	N/A	4" FLG	N/A	1.5"	N/A	C/F	N/A	3749	7400**	
HET 2500 ASME	2538	72.0"	76.0"	148"	150.5"	35.0"	N/A	45.0"	N/A	4" FLG	N/A	1.5"	N/A	C/F	N/A	3995	9000**	
HET 3000 ASME	2961	72.0"	76.0"	172"	174.5"	35.0"	N/A	45.0"	N/A	4" FLG	N/A	1.5"	N/A	C/F	N/A	4575	C/F	

**Note:** 125 PSI standard on all tanks, with the exception of HET 80, 120, and 200, which are 150 PSI standard. Custom sizes & linings are also available. Consult factory for details.

\* Manway comes standard on 42" diameter and larger tanks, and is optional on 30" and 36".

\*\* Vertical square I/J tank

Dimensions are approximate. Please consult factory before installation.

## STORAGE TANK COMPONENT DESCRIPTION

